

ENGEZER

SOLUÇÕES EM ANÁLISE DE
GASES

RLD10 Detector de vazamento de refrigerante

Tel.: (21) 3445.8120

E-mail: engezer@engezer.com.br

Site: www.engezer.com.br

(21) 97144.1593 

@engezer 

Engezer Spengezer 

sergio.engezer 



RLD10

Refrigerant Leak Detector

PINPOINTING LEAKS AS EASY AS ONE, TWO!

- Auto zeros when turned on
- LED panel indicates refrigerant leak concentration
- Two position sensitivity selector
- Audible tick rate
- Automatically detects all existing refrigerants and blends



RLD10 • Refrigerant Leak Detector

The RLD10 makes pinpointing leaks as easy as one, two! Detect leaking refrigerant using the high sensitivity mode then switch to the low sensitivity mode to pinpoint its source. If background noise makes the audible tic hard to hear, you can count on the color scaled LED indicators.

The RLD10 has the following features:

- Auto zeros when turned on
- Color scaled LED's indicate refrigerant leak rate
- Two position sensitivity selector
- Audible tick rate
- Long gooseneck probe
- One-hand operation
- Automatically detects all existing halogen refrigerants and blends
- One year limited warranty

Replacement Parts:

- Sensor TipRLDTG
- SensorRLDSENS

Optional Accessories:

- Soft Carrying CaseAC315
- Hard Carrying CaseAC506

Specifications

Power supply	One 9 volt battery
Sensor	Advanced ionization detection
Sensitivity	.5 oz. per year R134A
Indicators	Audible: Variable tick Visual: Scaled LED array
Warm-up	<10 seconds
Response time	<1 second
Duty cycle	Continuous
Battery life	Approximately eight (8) hours
Probe length	18 - 1/2"
Ambient operating conditions	32° to 102°F (0° to 40°C), 0 to 80% RH (noncondensing)



Caso queira adaptar este produto a suas necessidades usando um sistema de condicionamento, uma automação ou formando um produto, contate:

COMERCIAL@ENGEZER.COM.BR

**para mais informações ou preços*



ENGEZER

SOLUÇÕES EM ANÁLISE DE
GASES



(21) 97144.1593



@engezer



Engezer Spengezer



sergio.engezer